



Food and Agriculture Organization  
of the United Nations



## **FishStatJ Manual**

# **FishStatJ Manual**

Version 4.02.7 – August 2022

*Citation and disclaimer to be provided through PWS*

# CONTENTS

<b>1.About FishStatJ</b> .....	1
<b>2.Installation</b> .....	2
<b>2.1.Installing on Windows</b> .....	2
2.1.1.Windows requirements .....	2
2.1.2.32bit Windows installer .....	2
2.1.3.Using Windows auto-extract installer .....	3
2.1.4.Do not move or rename files.....	3
2.1.5.Adding FishStatJ to the Taskbar .....	4
<b>2.2.Windows troubleshooting</b> .....	5
2.2.1.Installation issues .....	5
2.2.2.How to check if your computer supports 64-bit .....	5
2.2.3.Diagnostic reporting.....	6
2.2.4.How to check that FishStatJ is not corrupted.....	6
<b>2.3.Installing on macOS</b> .....	7
2.3.1.macOS requirements .....	7
2.3.2.Installation.....	7
2.3.3.Authorization .....	8
<b>2.4.macOS troubleshooting</b> .....	9
2.4.1.Diagnostic reporting.....	9
<b>2.5.FishStatJ Privacy Policy</b> .....	10
<b>2.6.Workspaces (statistical data)</b> .....	11
<b>3.File Menu</b> .....	12
<b>3.1.Manage workspaces</b> .....	12
3.1.1.Installing a new workspace (download) .....	14
3.1.2.Deleting a workspace .....	19
3.1.3.Importing a workspace.....	19
<b>3.2.Open Dataset</b> .....	23
3.2.1.New data is available .....	24
<b>3.3.Close workspace</b> .....	25
<b>3.4.Export selection (CSV file)</b> .....	26
<b>3.5.Exit</b> .....	27
<b>4.Data display</b> .....	28
4.1.Displaying a dataset .....	28
4.2.Notes (if applicable).....	29
4.3.Toolbar icons .....	30
4.4.Row Details .....	30
4.5.Number of rows .....	30
4.6.Memory Status .....	30
<b>5.Edit Menu</b> .....	31
5.1.Select all .....	31
5.2.Select none .....	32
5.3.Copy selection .....	33
5.4.Preferences .....	34
5.4.1.General preferences .....	35
5.4.2.Data display .....	36

5.4.3.Data display – Number formatting .....	37
5.4.4.Data display – Symbols and Colors .....	38
5.4.5.Data export.....	39
5.4.6.Internet Access .....	40
5.4.7.Languages .....	41
<b>6.Data Menu .....</b>	<b>42</b>
6.1.Filter.....	42
6.1.1.Selection mode preferences .....	45
6.2.Aggregate .....	47
6.3.Columns... .....	50
6.4.Sort.....	54
6.5.Top/Other.....	56
6.6.Custom groups .....	59
6.7.Calculated columns.....	62
<b>7.Format Menu .....</b>	<b>67</b>
7.1.Column width.....	67
7.2.Number formatting.....	67
7.3.Symbols and Colors .....	67
<b>8.View Menu .....</b>	<b>68</b>
8.1.Show details .....	68
8.2.Grand totals .....	71
<b>9.Metadata Menu .....</b>	<b>73</b>
9.1.Show metadata... .....	73
9.2.Show notes.....	75
9.3.Show citation... .....	77
9.4.Show map.....	79
<b>10.Help Menu .....</b>	<b>81</b>
10.1.Getting Started .....	81
10.2.User Manual .....	81
10.3.About FishStatJ .....	82
<b>11.Frequently asked questions (FAQ) .....</b>	<b>83</b>
11.1.How to export data?.....	83
11.2.What does that symbol mean? .....	83
11.3.Why am I getting different numbers than those from the FAO Yearbook of Fishery and Aquaculture Statistics/SOFIA? .....	83
11.4.FishStatJ working offline? .....	84
11.5.Some historical data figures have changed. Why? .....	85
11.6.Where to find detailed notes for each dataset? .....	85
11.7.How often is the data/application updated?.....	85
11.8.FishStatJ is being flagged as a virus threat.....	86
11.9.How does FAO assign nationality to catches? .....	86
11.10.FishStatJ has a Log4j vulnerability? .....	87
<b>12.More on FishStatJ .....</b>	<b>88</b>
12.1.FishStatJ legal specifications .....	88
12.2.Bibliographic citation .....	88
12.3.Data versioning and Data revisions.....	88
12.4.FishStatJ workspace folder .....	89
12.4.1.FishStatJ workspaces .....	89
12.4.2.Workspace metadata folder.....	89

12.4.3.Workspace manual folder.....	89
12.5.Un-installing FishStatJ.....	90
12.6.FishStatJ update notification .....	90
12.6.1.Automatic update notification.....	90
12.6.2.update notification .....	91
12.6.3.Workspace download .....	92
12.6.4.FishStatJ manual download .....	92
12.7.Assistance and Contact.....	93

# 1.About FishStatJ

FishStatJ is a desktop application designed to disseminate FAO fishery statistical data to the world. FishStatJ's primary aim is to display, refine and export data. However, unlike a spreadsheet software it cannot modify the data, create graphs or perform advanced data analysis. One of FishStatJ's greatest strength is that it can display species according to several authoritative classifications, such as the International Standard Statistical Classification of Aquatic Animals and Plants (ISSCAAP) or the UN's Central Product Classification (CPC); and show the scientific name.

At the 23rd CWP meeting (2010), the prototype of FishStatJ was endorsed for full development and the first release of FishStatJ was delivered in 2011. FishStatJ is built using the Eclipse Rich Client Platform (Eclipse-RCP) tools. As such, it is a Java application, and requires that Java is installed on the computer. RCP allows to develop general purpose applications, which run on Windows and macOS.

FishStatJ build and improves on the features of FishStatPlus (its predecessor):

- all Fishery reference data is available (all FAO code lists with all attributes);
- all hierarchies are available (for view, and for filtering/aggregation);
- calculated columns of FishStatPlus are included;
- the software is cross-platform (Windows, Macintosh) ;
- data (workspaces) of dimensions can be defined as needed (flexible); and
- any data with fixed dimensions and yearly resolution can be loaded.

For the creation of workspace files (database files), a separate software called "FishStatJ Console" was developed.

In order to use the statistical data, the user has **to download and install the FishStatJ application** on his computer (more details follow).

## 2.Installation

### 2.1.Installing on Windows

To download FishStatJ for Windows, go to [fao.org/fishery/statistics/software/fishstatj/en](http://fao.org/fishery/statistics/software/fishstatj/en).

#### FishStatJ - Software for Fishery and Aquaculture Statistical Time Series

---

FishStatJ is a Windows and Mac application that anyone can use to access FAO's Fisheries and Aquaculture statistics. They include datasets on production, trade and consumption. Data can be extracted and aggregated according to different level of details and international standard classifications. It consists of a main application and several workspaces that include the datasets.

[List of data available within FishStatJ](#) ↔

#### FishStatJ key features

- datasets browsing, data mining and reporting
- data querying, filtering, grouping and aggregation

#### Installing FishStatJ v4.01.0

Download FishStatJ

- for [Windows64-bit \(7,8,10\) auto-extract \(Instructions\)](#)
- for [macOS](#)



#### Related topics

---

[Statistics - Introduction](#)

#### 2.1.1.Windows requirements

FishStatJ is compatible with Windows 10; 64-bit version; cannot work with Windows 32-bit. The troubleshooting section below describes how to check your version of Windows.

Starting with FishStatJ version 4.01 Java 11 (OpenJDK project) is included with FishStatJ.

The FishStatJ needs about 1.5GB of disk space (400MB for the application, and the rest for data).

FishStatJ requires between 1Gb and 4GB of memory, depending on the size of the dataset used.


#### 2.1.2.32bit Windows installer

Starting with version 4.01.0 (as of March 2021) 32-bit Windows Operating system is not supported any more.




### 2.1.3.Using Windows auto-extract installer

When running the auto-extract installer (**FishStatJ\_Installer.exe**), it will ask for the following permission:



After clicking on the **Yes** button, the installer will extract the application to C:\FishStatJ, and immediately launch FishStatJ after the extraction is complete.



No further action is required.


**Note:** The **FishStatJ\_Installer.exe** file is not a real installer but a 7-Zip auto extract archive. As such, it does not require administrative permissions. I requires permissions to create the FishStatJ folder on the C:\ disk; this permission is usually available using accounts that lack Administrative rights.

### 2.1.4.Do not move or rename files


Please do not move or rename the files and folders, this will break the program. To resolve a corruption issue, delete the entire folder and it's content: C:\FishStatJ and run the Install.exe program again to extract the whole folder structure.

## 2.1.5. Adding FishStatJ to the Taskbar

Applications can be added to the Taskbar (usually on the bottom of the screen) by right-clicking on the **FishStatJ.exe** file and select the **Pin to Taskbar** option.



A FishStatJ shortcut has now been added to the Taskbar:



## 2.2.Windows troubleshooting

### 2.2.1.Installation issues


FishStatJ is a 64-bit software, and therefore requires Windows 10, 64-bit. In the case the FishStatJ application does not start (show the FishStatJ logo, then the main menu); perform the following steps to delete and re-copy the application:

- Before launching the EXE Auto-Extract to install a new version, exit any open instance of FishStatJ (**File** → **Exit**) so that the files of the new version can be copied.
- Delete the FishStatJ folder inside the C:\ disk. using Windows explorer.
- Re-run the FishStatJ auto-extract EXE

### 2.2.2.How to check if your computer supports 64-bit

FishStatJ is a 64-bit software, and therefore requires 64-bit Windows. The reason for this 64-bit requirement relates to the memory handling required for loading statistical data.

To check if your computer is running Windows 64-bit, please refer to the following Microsoft Support webpage: [support.microsoft.com/en-us/help/13443/windows-which-operating-system](https://support.microsoft.com/en-us/help/13443/windows-which-operating-system)




**System type** shows whether your computer is running a 32- or 64-bit version of Windows.

### 2.2.3. Diagnostic reporting

In case you encounter an issue with the application, please turn on **Log diagnostic reporting**, which you can find in the **Edit** → **Preferences** menu and then exit and re-launch FishStatJ.

When you turn on **Log diagnostic reporting** in the **Preferences**, FishStatJ will check and create a log report if the program encountered an error. Please do share this report with us – it helps us to diagnose problems.



We are working constantly to update our data; publishing workspaces with the latest fisheries and aquaculture data. We are grateful for any type of feedback, since it allows us to improve the application.

### 2.2.4. How to check that FishStatJ is not corrupted

We have included a text file (TXT format), on the web-page which provides the hash for the FishStatJ\_Installer.exe (auto-extract). Once extracted, you find a TXT file with the FishStatJ.exe hash in the C:\FishStatJ folder.

The hash is calculated using the CERTUTIL tool, which is standard on Windows 10.

To check, open a DOS window, then change to the directory using the CD command. Then run CERTUTIL --hashfile FishStatJ.exe

or CERTUTIL --hashfile FishStatJ\_Installer.exe.

This will provide the hash calculated from the EXE file, which you compare against the hash we provide.

This way you can be sure, that the EXE files have not been tampered with.

## 2.3.Installing on macOS

To download the FishStatJ for macOS, please go to [fao.org/fishery/statistics/software/fishstatj/en](http://fao.org/fishery/statistics/software/fishstatj/en).

### FishStatJ - Software for Fishery and Aquaculture Statistical Time Series

---

FishStatJ is a Windows and Mac application that anyone can use to access FAO's Fisheries and Aquaculture statistics. They include datasets on production, trade and consumption. Data can be extracted and aggregated according to different level of details and international standard classifications. It consists of a main application and several workspaces that include the datasets.

[List of data available within FishStatJ](#) 

#### FishStatJ key features

- datasets browsing, data mining and reporting
- data querying, filtering, grouping and aggregation

#### Installing FishStatJ v4.01.0

Download FishStatJ

- for [Windows64-bit \(7,8,10\) auto-extract \(Instructions\)](#)
- for [macOS](#)



#### Related topics

[Statistics - Introduction](#)

### 2.3.1.macOS requirements

FishStatJ is compatible with macOS 10.13 (HighSierra) or later.

Starting with FishStatJ version 4.01 Java 11 (OpenJDK project) is included with FishStatJ.

The FishStatJ needs about 1.5GB of disk space (500MB for the application, and the rest for data).

FishStatJ requires between 1Gb and 4GB of memory, depending on the size of the dataset used.


### 2.3.2.Installation

After the FishStatJ application is extracted from the ZIP file, it can be launched directly run from the Desktop, or moved to the Applications folder.

The FishStatJ application is code-signed and starting with version 4.01 is also notarized with Apple. As it is not an application from the app store: at the first launch it **requires the actions below in order to obtain permission to run.**

### 2.3.3.Authorization

In order to authorize FishStatJ ,security settings need to be adjusted in **System Preferences** → **Security & Privacy**; to change settings the Preferences Panel must be unlocked first.




For details on macOS security refer to <https://support.apple.com/en-us/HT202491>.  
The next step is to download workspaces, for this please refer to section 3.1.1.

## 2.4.macOS troubleshooting

### 2.4.1.Diagnostic reporting

In case you encounter an issue with the application, please turn on **Log diagnostic reporting**, which you can find in the **Edit** → **Preferences** menu and then exit and re-launch FishStatJ.

When you turn on **Log diagnostic reporting** in the **Preferences**, FishStatJ will check and create a log report if the program encountered an error. Please do share this report with us – it helps us to diagnose problems.



We are working constantly to update our data; publishing workspaces with the latest fisheries and aquaculture data. We are grateful for any type of feedback, since it allows us to improve the application.

## 2.5.FishStatJ Privacy Policy

FishStatJ does not process or store any user input, and does not collect any user related information.

FishStatJ downloads a small file at startup, this requires an internet connection:

- in order to inform the user about program updates
- in order to present the user with a list of workspaces available for download

This is described in detail in section [12.6](#) (update notification).

The internet connection is used to download workspaces (statistical data), as described in section [3.1](#) (manage workspaces). The download of workspaces is entirely under the control of the user. The download location can be customized in general preferences [5.4.1](#).

The location of the data is described in detail in section [12.4](#) (workspace folder).

The workspace folder contains the application log. The log contains information about the internal state of the program - no user information. The log can be viewed by the user as described in section [2.2.4](#) (diagnostic reporting); section [12.4](#) (metadata folder).

FishStatJ does save program settings modified by the user. The settings are managed using preferences as described in section [5.4](#) (Preferences).

Eclipse RCP (Rich Client Platform) is Java based, and as such FishStatJ requires OS permissions to run the Java and Eclipse IDE code. The open-source OpenJDK Java is included with FishStat.

FishStatJ is designed to run using normal user permissions on Windows and macOS; elevated permissions are not required.



## 2.6.Workspaces (statistical data)

Workspace files carry the statistical data. You can install an unlimited number of workspaces on a computer. However, FishStatJ can only work with one workspace at a time.

A workspace can contain one or more datasets. For the dissemination of data, workspaces are compressed into workspace files (.wks extension). FishStatJ downloads and extracts/installs workspaces automatically.

We currently offers several different workspaces files, which contain the following datasets:

- the **Global Production** workspace which contains:
  - Global Production
  - Capture Production
  - Aquaculture Production
- the **Regional workspace** with contains:
  - CECAF (Eastern Central Atlantic)
  - GFCM (Mediterranean and Black Sea)
  - RECOFI capture production
  - SEATL Southeast Atlantic Capture Production
- the **Food Balance** workspace which contains:
  - Food Balance Sheet
  - Population data
- the **Commodities** workspace which contains:
  - Fisheries Commodities Production and Trade


Please refer to section 3.1 (manage workspaces) for loading data into FishStatJ.

## 3.File Menu

### 3.1.Manage workspaces

The **Manage workspaces** menu allows the user to manage the workspaces:


- Open workspaces already installed.
- Download and install workspaces (from the FAO website).
- Delete workspaces installed on the computer.



When you click on **Manage workspaces**, the **Workspaces Manager** window appears on the screen. There, two kind of workspaces are displayed:

- Workspaces in **red color**, are *not installed* on the computer (also if there is a new version available).
- Workspaces in **blue color** are *installed* on the computer.

The screenshot below shows that version 2018.1.0 of the “FAO Global Fishery and Aquaculture Commodities Statistics” workspace is installed on the computer:




Workspaces already installed on the local disk can be **Opened** for viewing the data, or **Deleted** from the computer.

Manually downloaded workspaces can be imported using the **Import** button.


Workspaces that are already installed are not shown as available for download.

### 3.1.1. Installing a new workspace (download)


To install a new workspace, select an uninstalled (in red) workspace and click on the **Download...** button.




Clicking on the **Download** button will open a new window, the workspace import wizard:




A progress bar appears during the download:




Once the file has finished downloading, press the **Next** button to install it on your computer.




If an older version of the data is present (this typically happens after the yearly release of updated workspaces from FAO), FishStatJ will ask if the new version should overwrite the old version – or keep both (resulting in two versions of the same data installed). Select the option most appropriate for you, and click **Next**.



Please wait while the workspace is installing.




When the installation is complete, click the **Finish** button.



After clicking on **Finish**, the **Dataset browser** window appears. To start using your newly installed workspace, please refer to section 3.2 (open dataset) below.



### 3.1.2. Deleting a workspace




In the **Workspaces manager**, selecting a workspace will show metadata for this particular workspace (Acronym, Version, Name, Description, Provider, and Location on disk). The selected workspace is permanently removed from your computer when you click on the **Delete** button.


### 3.1.3. Importing a workspace

The **Import...** button allows the user to import manually downloaded workspaces into FishStatJ. However, since FishStatJ is able to download workspaces files, most users do not need to download and import workspaces manually.


If you need to import a workspace manually, click on the **Import...** button of the **Workspaces Manager**.




A file explorer window will appear, inviting you to select the .fws file corresponding to the workspace you wish to import. Select the .fws file and click on the **Open** button.




In the window that appears, click on the **Next >** button.



The following window is displayed, confirming that you have selected a valid workspace file and inviting you to install it on your computer. To do so, click on the **Next >** button.




Once FishStatJ confirms that the workspace installation is complete, click on the **Finish** button to go back to the interface and open the workspace.




## 3.2.Open Dataset...

**Note:** This option is only available when a workspace is currently open in FishStatJ.




Selecting this option will present the **Dataset browser** window, where datasets may be opened and brought into FishStatJ for viewing.

Once you have opened a dataset, the **Manage workspaces** item under the **File** menu is disabled (or dimmed); until you close the active workspace by clicking on the **Close workspace** item.



Selecting a dataset by clicking on the items listed on the left-side of the window will present the associated metadata on the right-side of the window. Select a dataset and click on the **OK** button to open the dataset content.

### 3.2.1. New data is available




In case there is a newer version of workspace available published for download the program will ask if you want to open the currently installed (2020.1.0 in this example) or download the new version.

Clicking on “New Version” will open the manage Workspace dialog - which shows the new versions available for download in red color.


**Note:** This function is not available when working off-line; as it requires an active internet connection.

### 3.3. Close workspace



Selecting this item will close the current workspace and all datasets and that are active within this workspace.

**Note:** The **Close workspace** option saves settings for all active datasets. Next time you launch FishStatJ, saved settings are applied. If you do not want a dataset to open automatically next time you open FishStatJ, just close it using the **Close icon** on the dataset panel:




**Note:** Filtering and aggregation settings are also recorded for each dataset; and automatically re-applied when you launch FishStatJ next time.


If the **Save working session on exit** option (located in **Edit** → **Preferences**) is active, when FishStatJ restarts the datasets that were open when the user exited the application will automatically reopen.

### 3.4.Export selection (CSV file)...

Selecting this option will save all selected rows into a comma-separated values (CSV) file:




A **Save As** pop-up window will appear so that all selected rows may be saved into a .csv file on a given location of the hard drive.



When the save of the selected records into a .csv file is complete, a confirmation message will appear:






Settings for export of CSV files are managed in **Edit** → **Preferences** → **Data Export**. See section 5.4(data export) for more information.

**Note:** The CSV file shows the period (years) in brackets, for example “[2022]”. This is a statistical standard also used by FAOSTAT. The reason is to prevent Excel from recognizing the period as a number which can be aggregated.

### 3.5.Exit



Selecting this option will close the FishStatJ program.

# 4.Data display

## 4.1.Displaying a dataset

When a dataset is open, the main window of FishStatJ looks like this:

The screenshot displays the FishStatJ application window titled "FishstatJ - FAO Global Fishery and Aquaculture Production Statistics". The main data table is titled "Global capture production - Quantity (1950 - 2016)". The table has columns for "Country (Country)", "Species (ASFIS spe...)", and years from 2008 to 2015. The data is filtered to show only Albania. The species listed include Freshwater fishes, Angelsharks, Atlantic bluefin tuna, Atlantic bonito, Barracudas, Bighead carp, Bleak, Blue and red shrimp, Blue whiting, Bluefish, Bogue, Caramote prawn, Catsharks, Common carp, Common cuttlefish, Common dace, Common dentex, Common octopus, Common sole, Common spiny loach, Common squids, Croakers, and Crucian carp. The production values are shown in thousands of metric tons (F). A "Row Details" panel at the bottom shows a grid of years from 1950 to 1965, with the current row highlighted for 2008. The status bar at the bottom right indicates "366M of 1077M".

Country (Country)	Species (ASFIS spe...)	2008	2009	2010	2011	2012	2013	2014	2015
Afghanistan	Freshwater fishes ...	1000 F	1000 F	1000 F	1000 F	1000 F	1000 F	1000 F	1000 F
Albania	Angelsharks, sand...	23	14	78	12	5	5	4	4
Albania	Atlantic bluefin tu...	-	50	-	0	-	9	34	40
Albania	Atlantic bonito	27	21	23	12	5	4	3	27
Albania	Barracudas nei	...	...	7	...	...	...	...	...
Albania	Bighead carp	24	5	...	23	12	13	10	16
Albania	Bleak	190	530	505	360	195	200	210	80
Albania	Blue and red shrimp	...	...	...	...	...	...	...	...
Albania	Blue whiting(=Po...	-	-	-	-	-	-	-	-
Albania	Bluefish	-	-	-	-	-	-	-	-
Albania	Bogue	132	154	80	88	55	50	78	90
Albania	Caramote prawn	23	20	228	9	19	24	33	22
Albania	Catsharks, nurseh...	...	...	...	...	...	...	...	...
Albania	Common carp	371	214	335 F	450	398	418	434	480
Albania	Common cuttlefish	62	126	98	90	80	85	75	82
Albania	Common dace	8	4	...	4	4	5	5	5
Albania	Common dentex	32	43	25	22	14	13	11	15
Albania	Common octopus	82	109	47	113	165	170	173	124
Albania	Common sole	63	69	120	68	79	62	44	71
Albania	Common spiny lo...	3	1	...	2	...	...	...	...
Albania	Common squids ...	107	60	64	52	76	92	105	134
Albania	Croakers, drums ne	2	8	1	2	4	3	5	4
Albania	Crucian carp	380	208	225 F	230	90	90	439	164

## 4.2. Notes (if applicable)

Country notes are now made visible in the data display through a red triangle. In the past notes have been published in the annual statistical yearbook (PDF version).

- The red triangle only shows, if the object has note text defined.

Country (Name)	Continent (Name)	ASFIS species (Name)	FAO major fishing area	Environment (Name)
➤ Afghanistan	Asia	Cyprinids nei	Asia - Inland waters	Freshwater
➤ Afghanistan	Asia	Rainbow trout	Asia - Inland waters	Freshwater
Albania	Europe	Bighead carp	Europe - Inland waters	Freshwater
Albania	Europe	Common carp	Europe - Inland waters	Freshwater
Albania	Europe	Crucian carp	Europe - Inland waters	Freshwater
➤ Algeria	Africa	Barbel	Africa - Inland waters	Freshwater
➤ Algeria	Africa	Bleak	Africa - Inland waters	Freshwater
➤ Algeria	Africa	Caramote prawn	Mediterranean and...	Brackishwater
➤ Algeria	Africa	Common sole	Mediterranean and...	Brackishwater

The notes are visible by selecting a row, and then right-clicking on the Country:

**China**

The 2000-2002 aquaculture production data for "Oriental river prawn" (*Macrobrachium nipponense*) have been included based on published reports. The figures for 2003-2008 have been provided by the national reporting office.

For statistical purposes, the data for China do not include Hong Kong Special Administrative Region (Hong Kong SAR), Macao Special Administrative Region (Macao SAR) and Taiwan Province of China.

Data for "Turbot" for 2003-2017 were subtracted from "Lefteye flounders nei" as FAO estimates.

Attribute	Value	Description
▶ Name		Country name
ISO3 code	CHN	ISO3 code
ISO2 code	CN	ISO2 code
Internal identifier	41	Internal identifier
▶ Official name		Official name
Code UN (M49)	156	Code UN (M49)
FAO 12 characte...	China	FAO 12 characters code

OK

The note text can be exported using copy/paste.


### 4.3. Toolbar icons

The toolbar icons on the left side provide quick access to the data tools. These are also exposed in the **Data menu**, where you also find a detailed explanation.

The toolbar icons on the right side provide quick access to the dataset attachments. These are also exposed in the **Metadata menu**, where you also find a detailed explanation.

### 4.4. Row Details

Selecting/highlighting a row (as shown above) will present the yearly data values on the lower part of the window (as shown under the **Row Details** tab).




### 4.5. Number of rows

The number of rows on display is shown in the lower-right part of the window. This number depends on the filtering criteria chosen by the user; Filtering is explained in section 6.1 (Filter).




### 4.6. Memory Status

The memory bar shows the state of the Java heap memory, which is a feature of RCP applications. This feature is useful for troubleshooting only.



# 5.Edit Menu

## 5.1.Select all




Clicking on this option will select all the rows in the currently open dataset:

The screenshot shows the 'Global aquaculture production - Value (1984 - 2016)' dataset in the FishstatJ application. All rows are selected, and the table displays production values for 1984 and 1985.

Country (Country)	Species (ASFIS spe...	Aquaculture area (...	Environment (Envi...	1984	1985
Afghanistan	Cyprinids nei	Asia - Inland waters	Freshwater	225	225
Afghanistan	Rainbow trout	Asia - Inland waters	Freshwater	60	60
Albania	Bighead carp	Europe - Inland w...	Freshwater	...	0
Albania	Common carp	Europe - Inland w...	Freshwater	25	50
Albania	Crucian carp	Europe - Inland w...	Freshwater	25	25
Albania	European seabass	Mediterranean an...	Marine	...	...
Albania	Freshwater fishes ...	Europe - Inland w...	Freshwater	2.5	15
Albania	Gilthead seabream	Mediterranean an...	Marine	0	0
Albania	Grass carp(=White...	Europe - Inland w...	Freshwater	...	...
Albania	Kuruma prawn	Mediterranean an...	Marine	0	0
Albania	Mediterranean m...	Mediterranean an...	Marine	588.9	586.3

## 5.2. Select none



Clicking on this option will deselect any selected row in the currently open dataset:


The screenshot shows the FishstatJ application window with the full dataset table displayed. The table has columns for Country, Species, Aquaculture area, Environment, and years 1984 and 1985.

Country (Country)	Species (ASFIS spe...	Aquaculture area (...	Environment (Envi...	1984	1985
Afghanistan	Cyprinids nei	Asia - Inland waters	Freshwater	225	225
Afghanistan	Rainbow trout	Asia - Inland waters	Freshwater	60	60
Albania	Bighead carp	Europe - Inland w...	Freshwater	...	0
Albania	Common carp	Europe - Inland w...	Freshwater	25	50
Albania	Crucian carp	Europe - Inland w...	Freshwater	25	25
Albania	European seabass	Mediterranean an...	Marine	...	...
Albania	Freshwater fishes ...	Europe - Inland w...	Freshwater	2.5	15

## 5.3.Copy selection

Country	Species	Region	Environment	1984	1985
Afghanistan	Rainbow trout	Asia - Inland waters	Freshwater	225	225
Afghanistan	Rainbow trout	Asia - Inland waters	Freshwater	60	60
Albania	Bighead carp	Europe - Inland w...	Freshwater	...	0
Albania	Common carp	Europe - Inland w...	Freshwater	25	50
Albania	Crucian carp	Europe - Inland w...	Freshwater	25	25
Albania	European seabass	Mediterranean an...	Marine	...	...
Albania	Freshwater fishes ...	Europe - Inland w...	Freshwater	2.5	15
Albania	Gilthead seabream	Mediterranean an...	Marine	0	0
Albania	Grass carp(=White...	Europe - Inland w...	Freshwater	...	...
Albania	Kuruma prawn	Mediterranean an...	Marine	0	0
Albania	Mediterranean m...	Mediterranean an...	Marine	588.9	586.3

Selecting this option will copy all selected rows into the clipboard. When the copy of the selected records into the clipboard is complete, a confirmation message will appear:




This option is useful if you intend to copy the selected rows directly into an opened spreadsheet.


The settings related to how data is copied to the clipboard are managed in **Edit** → **Preferences** → **Data Export**. See section 5.4 (data export) for more information.

## 5.4. Preferences

FishStatJ's **Preferences** include a range of settings that can be modified by the user. They can be accessed (i) from the **Edit** menu...




... and (ii) from the toolbar by clicking on the **Preferences icon**.



The **Preferences window** is presented below. Preferences are grouped in five categories, which are listed on the left side of the window. Specific options for each Preferences category are listed on the right side of the window.



## 5.4.1. General preferences



The **General preferences** options are the following:

- **Save/Load timeseries settings on exit/open** controls if the time series settings (like filtering, aggregation, column settings) are automatically saved (when exiting FishStatJ) and loaded (when launching the application).
- **Synchronize timeseries within the same dataset:** This is useful for Aquaculture data, to keep the time series of Quantity and Value in sync. Any filtering/aggregation settings will be applied to both time series.
- If **Log diagnostic reporting** is enabled, FishStatJ will read the log-file and check for any errors every time the application starts. In case the logs contain any program errors, it copies the last two months of logs into a file called mail.txt and ask the user to send this file to us for analysis. If the Outlook software on Windows is installed, FishStatJ automatically prepares the e-mail message. This option is disabled by default.

**Note:** FishStatJ does not automatically submit any log information. You can check the content of the text file before sending, and you have to (manually) send the file to FAO (refer to section 12.4.2).

In case of problems, the log analysis is useful to understand the cause of the problem. This helps us to fix the problem for the user reporting the problem—and to improve the quality for all users.


- **Workspace download location** allows to set the location where FishStatJ downloads workspaces before they are installed. We added this setting because some users reported that the Downloads folder does not exist on their PC.

Refer to section 12.4 for details on the log location, and FishStatJ workspaces.

## 5.4.2.Data display

The **Data display** preferences allows the user to specify:


- If the dataset panel automatically centers on the last column of the data each time it a dataset is loaded (set by default).
- Whether the width of the columns that contain values is automatically adjusted, or a fixed width (as determined by the user).
- If the dimension column header shows the attribute name (the default), or a generic dimension name



**Note:** If the column width display is set too small so that the observations are not readable, an easy solution is to set a column width of 60.


### 5.4.3.Data display – Number formatting

**Number formatting** options control how values are shown (i.e. set the number of digits before and after decimals; use point or comma as decimal separator; use decimal or scientific notation). It is important to note that these formatting preferences are used for display and when exporting data.




## 5.4.4.Data display – Symbols and Colors

**Symbols and Colors** options control how data symbols are shown (set color and symbol display). It is important to note that these formatting preferences are used for display and when exporting data.



## 5.4.5.Data export

This menu includes several options that set the modalities of data exports.



- **Export tables headers:** when selected, headers are exported.
- **Split values and symbols in two columns.** This is to avoid issues when analyzing the data after exporting it. Indeed, mixing symbols and figures within the same cells in a spreadsheet can make data analysis impossible, notably because the spreadsheet software will not recognize cells as numbers if these contain non-numerical characters.
- **Export selection criteria:** will add the filtering/aggregation settings to the export.
- **Don't export symbols.** This is to avoid issues when analyzing the data after exporting it. Indeed, mixing symbols and figures within the same cells in a spreadsheet can make data analysis impossible, notably because the spreadsheet software will not recognize cells as numbers if these contain non-numerical characters.
- **Export with totals on selected rows.**
- **Export citation.** See section 9.3.
- **Re-adjust the preferences on each export:** selecting this will show a dialog window before each export operation, to make sure that the proper export settings are selected before each data export.


## 5.4.6. Internet Access

The preferences regulating Internet access by FishStatJ are listed below:

- The **Settings for version download** are described in detail in section 12.6 (update notification).
- **Use Proxy** is provided in case the network is protected with a proxy server. It allows FishStatJ to download the current information (program version and workspaces versions) and download workspaces (data) using a proxy server. We added proxy settings as requested by some users.

The use of proxy is controlled with the **use Proxy** checkbox. Proxy server IP address and port number fields are required (must be filled) if proxy is activated.


The Proxy user ID and Proxy Password fields can be left empty.




The screenshot shows the 'Preferences' dialog box with the 'Internet access' section selected. The 'Settings for version download' section contains a text field for the URL, which is set to 'http://www.fao.org/fishery/static/FishStatJ/current\_version.xml'. The 'Proxy for version and workspace download' section includes a checkbox for 'use Proxy' (which is unchecked), and four text input fields: 'Proxy IP address' (10.0.0.1), 'Proxy Port number' (80), 'Proxy user ID' (empty), and 'Proxy Password' (empty). At the bottom of the dialog, there are buttons for 'Restore Defaults', 'Apply', 'Apply and Close', and 'Cancel'.

## 5.4.7.Languages

The language menu allows the user to change the language in which FishStatJ is displayed.




A familiar popup window will appear if the user tries to change the language. Click on the **Yes** button to restart the application.




# 6.Data Menu

## 6.1.Filter...

The timeseries filter becomes enabled once a dataset is open. **Filter** can be accessed (i) from the **Data** menu...




... and (ii) from the toolbar by clicking on the **Filter icon**.





Selecting **Filter** will open the **Time series filtering** window:



On the left side the items are *included* on the dataset panel, on the right side the items are *excluded* from the dataset panel. The **Include** side is empty by default, meaning that all items are shown.

Items available for filtering depend on the dimensions of the dataset loaded. In the example above, available filters are Country, Species and Fishing area. Australia is the only country selected in this example.

The arrow buttons copy the selected items from left-to-right or from right-to-left, according to the direction of the buttons:




The double-arrows copy all items in the direction indicated:




Clicking **OK** will activate the filter and refresh the data display in the main window.

Right-clicking on an item will display a quick selections menu:

- **Select all**
- **Deselect all**
- **Invert selection**
- **Choose attribute** allows to select the attribute used for the Filter dialog. This setting is remembered by FishStatJ:




- **Details on [name of item]** shows details on the selected item:




### 6.1.1. Selection mode preferences


The **Time series filtering** window includes a button to open the **Selection mode preferences**:



It will bring up the **Selection Preferences** window:



A **Dimension value filter** can be defined for each of the **Dimensions**. The filter controls the list of items shown in the **Time series filtering** window.




**All** will show all items included in that particular workspace.

**Only those referenced** will show only reference objects which appear in the timeseries.


**Note:** to apply new settings, a restart of FishStatJ is required.


## 6.2.Aggregate

The **Aggregate** function is available once a dataset is open. It can be accessed (i) from the **Data** menu...



...and (ii) from the **Aggregate icon** in the dataset toolbar:






FishStatJ memorizes aggregation settings for each dataset.

On the **Time series aggregation** popup window, three modes of aggregation are available for each data dimension.

- When **Detailed** is selected, the dimension is effectively not aggregated.
- When the user selects **Grouped**, the aggregation can be made on the basis of each individual group associated with the dimension. Groups can also be **Handpicked**.



- When **Aggregated** is selected, all the data associated to a given dimension is aggregated.

As an example, grouping the Country dimension by Continent while aggregating Species and Fishing area, produces the following result:


The screenshot shows the FishstatJ software interface. The title bar reads "FishstatJ - FAO Global Fishery and Aquaculture Production Statistics". The menu bar includes "File", "Edit", "Data", "Format", "View", "Metadata", and "Help". The toolbar contains various icons for data manipulation. The main window title is "Global capture production - Quantity (1950 - 2016)". Below the title bar is a table with the following data:

Country (Continent)	Species (ASFIS spe...	Fishing area (FAO ...	Unit (Unit)
Africa	All	All	Tonnes
Americas	All	All	Tonnes
Asia	All	All	Tonnes
Europe	All	All	Tonnes
Oceania	All	All	Tonnes
Others	All	All	Tonnes


## 6.3.Columns...

This function allows the user to change the columns (attributes) that are used to view the dataset. A **Preferences** panel is used, because the settings are remembered.


The **Columns** function can be accessed (i) from the **Data** menu...



... and (ii) from the toolbar by clicking on the **Columns** icon.








For each dimension, columns can be added, modified and removed by clicking on the **New...**, **Edit...** and **Remove...** buttons, respectively.

**Note:** For species, when the common name is not available, the scientific name will be shown instead.


**Note:** When a dimension is aggregated, all attributes in that dimension are changed for the duration of the aggregation setting to show the aggregation group.

For example if you configure to display Country(Name) and Country(ISO3-Code) and then aggregate by Continent, both columns show Continent(Name) for as long as the aggregation is active.

When creating a new column or modifying an existing one, the Concept used to display a given Dimension can be changed by selecting **Concept**:




For each Concept, the **Attribute** can be selected:




Example: for the **Species** dimension, the common names used to display species can be replaced with the corresponding scientific names by selecting the **Scientific name** attribute.

**Periods** are the years on display, which may be changed, as shown below:




## 6.4.Sort...


The **Sort** function can be accessed (i) from the **Data** menu...



... and (ii) from the toolbar by clicking on the **Sort icon**.




The **Sort** window allows to choose how to sort the data. Sorting can be different from the columns shown on the display: for example it is possible to display the Species dimension by ISSCAP group, but sort it by Commodity. The sort ordering (i.e. ascending or descending) is selected using the **Direction** options on the right end of the window.




When using multiple sorting criteria, higher priority will be given to the criteria that are positioned higher in the list order.

## 6.5.Top/Other...

The **Top/Other** function can be accessed (i) from the **Data** menu...



... and (ii) from the toolbar by clicking on the **Top/Other** icon.



The **Top/Other** menu allows selecting records by the following criteria:

- **Top** [number] of records;
- **Top** [percentage] of records; or
- **records greater than** [cut-off value].

You can enter selection value (number of records/percent of records/value greater). All records that do not meet the criteria are aggregated into others, this is why the function is called Top/Other.

Global production by production source - Quantity (1950 - 2016)						
Country (Country)	Species (ASFIS spe...	Production area (F...	Production source...	Unit (Unit)	2009	2010
Indonesia	Eucheuma seawee...	Pacific, Western C...	Aquaculture prod...	Tonnes	'91688	3399436
Others	Others	Others	Others	Others	73925....	163522898....

As an example, selecting the top 10 records for the year 1975 is shown below.

Top/Other selection

Top/Other selection

Select top records and groups everything else as "Other"

Dataset: Global production by production source

by field 1975

by measure Tonnes

All records

Top 10 records

Records comprising percent of total

Values and greater

OK Cancel

**Note:** The **Top/other** function automatically applies a filter for the selected measure; because different measures cannot be compared.


For example: The capture dataset contains measure Tonnes and Numbers. Selecting the measure (Tonnes, as shown) will filter by tonnes.




## 6.6. Custom groups

The **Custom groups** function allows the user to define specific groups of countries, species, fishing areas, and measures. Typically, such groups are created by users to avoid repeated filtering for groups that are part of common workflows.


**Custom groups** can be accessed (i) from the **Data** menu...




... and (ii) from the toolbar by clicking on the **Custom groups** icon.




**Note:** The **Custom groups** menu item is only available when a dataset is open.



A number of custom groups are predefined for some time series elements. The above screen shows the custom groups for the **Country** dimension, while the image below shows custom groups that already defined for the **Species** dimension.



When a new custom group is to be created with the **New...** button, the **New custom group definition** window appears on the screen.



When an existing custom group requires editing with the **Edit...** button, the **New custom group definition** popup is presented with the existing group members listed in the **Include** field.

A **Custom group name** and **Custom group description** can be entered in the lower part of the window. As a minimum the English field should be filled.





Calculated columns may be created (**New...**) or edited (**Edit...**) by clicking on the corresponding buttons. This opens the **Calculated columns definition** popup window.

**Calculated columns definition**  
Define a new calculated column

**Column name**

**Function**

Computes the arithmetic mean of the set of values. Uses the definitional formula:  
 $\text{mean} = \frac{\sum(x_i)}{n}$  where  $n$  is the number of observations.

**Parameters**

**Skipping parameters**

Skip unknown values  Yes  No


Skip estimated values  Yes  No

Skip negligible values  Yes  No

Skip zero values  Yes  No

**Function parameters**

Many statistical functions are available for calculated columns, as shown below:



When a calculated column is created, it is shown on the right side of the dataset panel:

The screenshot shows the FishstatJ interface with a dataset titled 'Global capture production - Quantity (1950 - 2016)'. The table displays data for various species in Albania from 1950 to 1953, along with a calculated 'Arithmetic mean' column. The 'Arithmetic mean' column is highlighted with a red border.


Country (Country)	Species (ASFIS spe...)	1950	1951	1952	1953	Arithmetic mean
Afghanistan	Freshwater fishes ...	100	100	100	100	703.73
Albania	Angelsharks, sand...	...	...	...	...	8.16
Albania	Atlantic bluefin tu...	-	-	-	-	2.69
Albania	Atlantic bonito	...	...	...	...	5.01
Albania	Barracudas nei	...	...	...	...	0.33
Albania	Bighead carp	-	-	-	-	2.12
Albania	Bleak	...	...	...	...	87.99
Albania	Blue and red shrimp	...	...	...	...	1.55
Albania	Blue whiting(=Po...	...	...	...	...	0.33
Albania	Bluefish	...	...	...	...	0.25
Albania	Bogue	...	...	...	...	113.64
Albania	Caramote prawn	...	...	...	...	20.15
Albania	Catsharks, nurseh...	...	...	...	...	0.1
Albania	Common carp	...	...	...	...	113.09
Albania	Common cuttlefish	...	...	...	...	21.39
Albania	Common dace	-	-	-	-	0.7
Albania	Common dentex	...	...	...	...	5.97

Record no. 8 of 21249 filtered rows 780M of 1104M




# 7.Format Menu

## 7.1.Column width




Selecting **Column width** will take the user to the **Data display** tab of the **Preferences** window. See section 5.4.2 for more information.

## 7.2.Number formatting



Selecting **Number formatting** will take the user to the **Data display** tab of the **Preferences** window. See section 5.4.3 for more information.


## 7.3.Symbols and Colors



Selecting **Symbols and Colors** will take the user to the **Data display** tab of the **Preferences** window. See section 5.4.4 for more information.

## 8.View Menu


The **View** menu is only enabled when a dataset is open, otherwise it is dimmed (not available).




### 8.1.Show details

Selecting or deselecting this option will turn on or off the detailed information that is displayed at the bottom of the FishStatJ main display.

The **Show details** option can be toggled on and off (i) from the **View** menu...



... and (ii) from the toolbar by clicking on the **Show details** icon.



Turning on this option will reduce the number of time series records on display. On the image below, the **Row Details** tab is turned on.

The screenshot shows the FishstatJ interface with the following data table:

Country (Country)	Species (ASFIS spe...	Fishing area (FAO ...	1950	1951	1952	1953
Albania	Blue and red shrimp	Mediterranean an...	...	...	...	...
Albania	Blue whiting(=Po...	Mediterranean an...	...	...	...	...
Albania	Bluefish	Mediterranean an...	...	...	...	...
Albania	Bogue	Mediterranean an...	...	...	...	...
Albania	Caramote prawn	Mediterranean an...	...	...	...	...
Albania	Catsharks, nurseh...	Mediterranean an...	...	...	...	...
Albania	Common carp	Europe - Inland w...	...	...	...	...
Albania	Common cuttlefish	Mediterranean an...	...	...	...	...
Albania	Common dace	Europe - Inland w...	-	-	-	-
Albania	Common dentex	Mediterranean an...	...	...	...	...
Albania	Common octopus	Mediterranean an...	...	...	...	...

The 'Row Details' panel at the bottom contains input fields for years 1950 through 1970. The status bar at the bottom indicates '21249 filtered rows' and '386M of 1005M'.

Deselecting this option will remove the 'details' shown at the bottom of the FishStatJ main display. In the image below, the details are not displayed:


Country (Country)	Species (ASFIS spe...	Fishing area (FAO ...	1950	1951	1952	1953
Albania	Blue and red shrimp	Mediterranean an...	...	...	...	...
Albania	Blue whiting(=Po...	Mediterranean an...	...	...	...	...
Albania	Bluefish	Mediterranean an...	...	...	...	...
Albania	Bogue	Mediterranean an...	...	...	...	...
Albania	Caramote prawn	Mediterranean an...	...	...	...	...
Albania	Catsharks, nurseh...	Mediterranean an...	...	...	...	...
Albania	Common carp	Europe - Inland w...	...	...	...	...
Albania	Common cuttlefish	Mediterranean an...	...	...	...	...
Albania	Common dace	Europe - Inland w...	-	-	-	-
Albania	Common dentex	Mediterranean an...	...	...	...	...
Albania	Common octopus	Mediterranean an...	...	...	...	...
Albania	Common sole	Mediterranean an...	...	...	...	...
Albania	Common spiny lo...	Mediterranean an...	...	...	...	...
Albania	Common squids ...	Mediterranean an...	...	...	...	...
Albania	Croakers, drums nei	Mediterranean an...	...	...	...	...
Albania	Crucian carp	Europe - Inland w...	...	...	...	...
Albania	Deep-water rose s	Mediterranean an				

21249 filtered rows | 379M of 1005M


## 8.2. Grand totals

Activating **Grand totals** will create one or two (depending on the dataset) additional tabs in the FishStatJ display that show grand totals for the time-series.

The **Grand totals** option can be toggled on and off (i) from the **View** menu...



... and (ii) from the toolbar by clicking on the **Grand totals icon**.



The new tab(s) will be opened at the bottom of the window, as shown on the image below:

The screenshot shows the FishstatJ interface. The main window displays a table of global capture production data for Albania from 1950 to 1970. Below this, two summary tabs are visible: 'Global capture production - Number' and 'Global capture production - Tonnes'. The 'Number' tab is active, showing a grid of values for each year from 1950 to 1970.

Year	1950	1951	1952	1953	1954	1955	1956	1957	1958	1959	1960	1961	1962	1963	1964	1965	1966	1967	1968	1969	1970
Number	19245806.9	21696672.7	23657310	24078236	25989307.14	27512275	29178593	29377727	30047392	32396833	34790181	38630192	42035679	42996371.1	47586827.1	48653613.4	52568635.8	56020668	59336231	57903206	63886816

For example, the **Global production by production source - Quantity** dataset (shows above) has two Grand total tabs (**Number** and **Tonnes**) because two types of units can be used to display the data.

**Note:** When selecting a grouped aggregation (refer to section 6.2) which has overlapping group members the total shown is not the sum of the data on display, but the sum of the underlying raw data. Overlapping means, that a dimension (for example country) of a statistical observation is present in more than one group. In this case, the observations (for example catch) of this country are counted for each of the groups of which the country is a member; but are only counted once for the total.

Examples of overlapping groups are economic groups or RFB (ac country can be member of several regional fishery bodies).


# 9. Metadata Menu

The **Show notes...**, **Show citation...** and **Show map...** items are enabled depending on the attachments that are available for the current dataset.


## 9.1. Show metadata...

Selecting this option will display the metadata about the time-series that is selected within FishStatJ.

Metadata can be accessed (i) from the **Metadata** menu...



... and (ii) from the toolbar by clicking on the **Metadata icon**.




An example of the window showing metadata is shown below:

Metadata
✕

**Metadata**

Global capture production - Quantity (1950 - 2016)



Metadata
Dimensions
Attachments
time series

**Global capture production**

Country Species Fishing area Unit

**Dimension** Country      **Acronym** COUNTRY

**Description** Country or territory

---

**Concept** Country      **Acronym** COUNTRY

**Description** Country or territory

UN_CODE	ISO_3_CODE	NAME.EN	NAME.FR	NAME.ES	ISO_2_CODE	ALPHA12_C
0	EUR	European Union	Union Europé...	Unión Europea	EU	EU
004	AFG	Afghanistan	Afghanistan	Afganistán	AF	Afghanistar
008	ALB	Albania	Albanie	Albania	AL	Albania
010	ATA	Antarctica oth...	Antarctique a...	Antartida otros	AQ	Antarctica
012	DZA	Algeria	Algérie	Argelia	DZ	Algeria
016	ASM	American Sam...	Samoa améric...	Samoa Americ...	AS	Amer Samo
020	AND	Andorra	Andorre	Andorra	AD	Andorra
024	AGO	Angola	Angola	Angola	AO	Angola
028	ATG	Antigua and B...	Antigua-et-Ba...	Antigua y Bar...	AG	Antigua Bar
031	AZE	Azerbaijan	Azerbaïdjan	Azerbaiyán	AZ	Azerbaijan
032	ARG	Argentina	Argentine	Argentina	AR	Argentina


Copy to Clipboard
OK




## 9.2. Show notes...

Selecting this option will display the notes attached to a dataset. Notes contain descriptions about the time-series that is selected within FishStatJ.

Notes can be accessed (i) from the **Metadata** menu...




... and (ii) from the toolbar by clicking on the **Notes icon**.



**Note:** The **Show notes** menu item is enabled and the **Notes icon** is shown when the current dataset has notes embedded.


An example of the **Notes window** is displayed below:



## 9.3.Show citation...

Selecting this option will display the dataset citation, allowing to copy/paste it for easy reference.

The dataset citation can be accessed (i) from the **Metadata** menu...




... and (ii) from the toolbar by clicking on the **Citation icon**.



**Note:** The **Show citation** menu item is enabled and the **Citation icon** is shown when the current dataset has a citation embedded.


An example of the **Citation window** is displayed below:



## 9.4. Show map...

Selecting this option will display the map attached to a dataset. Those maps usually represent FAO's fishing areas.

The Map can be accessed (i) from the **Metadata** menu...



... and (ii) from the toolbar by clicking on the **Map icon**.



**Note:** The **Show map** menu item is enabled and the **Map icon** is shown when the current dataset has a map embedded.

An example of the **Map window** is displayed below:

Global production - Map of fishing areas

Global production - Map of fishing areas


© FAO 2015  
The designations employed and the presentation of information in the map(s) are for illustration only and do not imply the expression of any opinion whatsoever on the part of FAO concerning the legal or constitutional status of any country, territory or sea area, or concerning the delimitation of frontiers or boundaries.

www.fao.org/fishery/area/search


OK

# 10.Help Menu

The **Help** menu is shown below. It gives access to additional tools, preferences and help related to the FishStatJ software.



## 10.1. Getting Started




The **Getting Started** item from the **Help** menu automatically downloads the Getting Started with FishStatJ manual and opens it. The manual is a portable document format (PDF) file.

- Windows requires Acrobat Reader to open PDF documents
- macOS can open PDF documents using the Preview application

**Note:** When working with unreliable internet access, we suggest to open the manual when an internet connection is available, as this will make it available in case of future connection interruptions.

## 10.2. User Manual




The **User Manual** item from the **Help** menu automatically downloads the FishStatJ manual and opens it. The manual is a portable document format (PDF) file.


- Windows requires Acrobat Reader to open PDF documents
- macOS can open PDF documents using the Preview application

**Note:** When working with unreliable internet access, we suggest to open the manual when an internet connection is available, as this will make it available in case of future connection interruptions.

## 10.3.About FishStatJ



This item presents FishStatJ information about the program version, legal use, and contacts for assistance. The **About FishStatJ** window is shown below:





# 11. Frequently asked questions (FAQ)

## 11.1. How to export data?

You can export data from FishStatJ in two different ways (for more information, refer to section 5.4):

- You can simply copy a selection of rows and paste it on an Excel file (with the right button menu or with the **CTRL + C** shortcut).
- Or you can go to **File** → **Export selection (CSV file)**...

You can configure how data and symbols are exported (or not exported) in **Edit** → **Preferences** → **Data export** (refer to section 5.4.5)

## 11.2. What does that symbol mean?

FishStatJ uses the following symbols for statistical data:

- ... Data not available; unobtainable; Data not separately available but included in another category
- Nil or zero
- 0 More than zero but less than half the unit used
- F FAO estimate from available sources of information
- nei Not elsewhere included

In FishStatJ, you can configure the color of the symbols in the panel:

**Edit** → **Preferences** → **Data Display** → **Symbols and Colors** (refer to section 4.4.4).

As for data and symbol export to Excel, please be informed that you can configure how data and symbols are exported (or not exported) in:

**Edit** → **Preferences** → **Data export**.

**Don't export symbols** is one of the options you can select (refer to section 5.4.5).

## 11.3. Why am I getting different numbers than those from the FAO Yearbook of Fishery and Aquaculture Statistics/SOFIA?

Trying to cover all products derived from fisheries activities, in both inland and marine waters, the FAO Fishery production datasets (capture and aquaculture), include some products which are not (or not directly) destined to food consumption, such as marine mammals, crocodiles, corals, pearls, mother-of-pearl, sponges and aquatic plants. Those products are excluded from the all country, regional and world

totals presented in FAO Yearbooks of Fishery Statistics as well as other FAO publications.


When viewing time-series data in FishStatJ, in order to obtain the same aggregates you must first filter the dataset using a Custom Group:

1. Open the **Time series filtering** window (**Data** → **Filter** or **F4**)
2. Click the **ASFIS Species** tab
3. Click the **Species selection groups of Yearbook/SOFIA** group
4. Click **Fish, crustaceans, molluscs...**
5. Click the single left arrow in order to move all selected species belonging to Fish, crustaceans, molluscs, etc. under the Include panel on the left.
6. Click on the **OK** button. The program will return you to FishStatJ's main window.

The aggregation grouping for capture and aquaculture datasets is mentioned in the dataset notes where applicable. Access to dataset notes is explained in section 9.2.

## 11.4. FishStatJ working offline?

When the download of the auto-update information fails, FishStatJ produces the following warning:



If there is no internet connection possible, FishStatJ will run but the following functions will not be available:

- The notification of a new program version is not available (Refer to section 12.6 for a detailed description of the auto-update notification, and a description of data download from the internet).
- No workspaces are shown for automatic download: the **Manage workspaces** dialog only shows workspaces already downloaded/installed (refer to section 3.1)
- Download of the user manual is not possible (refer to section 10.2)

Section 5.4.6 explains Internet access proxy configuration.

## **11.5. Some historical data figures have changed. Why?**

Refer to section 12.3 for a discussion on data revisions.

## **11.6. Where to find detailed notes for each dataset?**

Additional information about the statistics presented in each dataset collection are available in the General notes, accessible in **Metadata** → **Show metadata** → **Attachments** (or by clicking on top right button of data panel).

Refer to section 9.2 and 9.3 for viewing dataset notes and data citation.

## **11.7. How often is the data/application updated?**

We publish new data as soon as we receive the complete set from member countries and have completed our verification. Usually, datasets are updated once per year. The release time for Global Capture and Aquaculture Production is in the second quarter every year.

New or updated datasets will automatically show in the **Manage workspaces** menu; refer to section 3.1 for a detailed explanation.

When the FishStatJ application is launched, it will also check for updates – and inform you if there is a new version available for download; refer to section 11.6 for the auto-update notification.

Data update/revisions are explained in section 12.3; internet access is discussed in section 5.4.6.

## 11.8. FishStatJ is being flagged as a virus threat

We have received various reports indicating that the FishStatJ software has been falsely identified as being a virus threat. Indeed, we work hard for FishStatJ to be the best product possible, and we would not knowingly distribute an infected version.

Wikipedia defines a false-positive as a false alarm: [wikipedia.org/wiki/False\\_positives\\_and\\_false\\_negatives](https://en.wikipedia.org/wiki/False_positives_and_false_negatives).

If you receive such alert from your antivirus software, we suggest the following actions, in the following order:

- Please send us an e-mail ([Fish-Statistics-Inquiries@fao.org](mailto:Fish-Statistics-Inquiries@fao.org)), describing the antivirus software used, and the alert message received (this way we can double-check your download, and also warn other users).
- Please inform your virus software vendor and notify them of the 'false positive' indication. The vendor can then quickly investigate (check our download) and release an update to their virus definitions (definitions are patterns to detect infected software).
- If you think FishStatJ is corrupted, the best is to re-download and expand a fresh copy.

**NEVER consider deactivating your virus protection - that would be irresponsible in this digital age!**

## 11.9. How does FAO assign nationality to catches?

As established by the United Nations Statistical Commission in 1954, catches are assigned to the country of the flag flown by the fishing vessel. The flag State is also responsible for the provision of the relevant data to FAO and other organizations such as Regional Fishery Bodies (RFBs).

## 11.10.FishStatJ has a Log4j vulnerability?

FishStatJ is an [Eclipse RCP \(Rich Client Platform\)](#) application, and log4j is included in FishStatJ as part of the Eclipse platform.

### Vulnerability Status:

The vulnerability applies only to log4j2 but Eclipse/FishStatJ uses log4j(-1) v2.12. The safest mitigation for the vulnerability is to remove or disable JNDI, but Log4j does not have any JNDI functionality.

**Log4j lacks JNDI, no mitigation effort is possible, and therefore log4j is not an attack vector.**

Keep in mind, FishStatJ is very different from a web-server, where the hacker can input/control what is written to the log. FishStatJ is a data query tool, and there is absolutely no data entry, no text entry, by the user. Furthermore, FishStatJ is a user application – runs in user space; and does not use or require elevated privileges. As such, the log4j update is a low priority for the Eclipse IDE project. Recall, the Eclipse IDE is an open-source project, which has no regular funding/support.

### Summary:

**The log4j2 vulnerabilities, in particular, CVE-2021-44228 and CVE-2021-44832, do not apply to FishStatJ.**

We are constantly updating FishStatJ, and the log4j plugin will be updated to log4j2 as soon as this update for the Eclipse IDE is available.

# 12. More on FishStatJ

## 12.1. FishStatJ legal specifications

The FishStatJ software is provided free of charge to member countries of the Food and Agriculture Organization of the United Nations (FAO). It may be installed on personal or company computers without restriction or license. The statistics contained in this package may be used and published freely provided that the source is cited as FAO.

## 12.2. Bibliographic citation

FAO encourages the use, reproduction and dissemination of material in this information product. Except where otherwise indicated, material may be copied, downloaded and printed for private study, research and teaching purposes, or for use in non-commercial products or services, provided that appropriate acknowledgement of FAO as the source and copyright holder is given and that FAO's endorsement of users' views, products or services is not implied in any way.

All requests for translation and adaptation rights, and for resale and other commercial use rights should be made via [fao.org/contact-us/licence-request](https://www.fao.org/contact-us/licence-request) or addressed to [copyright@fao.org](mailto:copyright@fao.org).

When quoting FishStatJ data, please use the reference that you can find in the General Notes attached to each dataset (**Metadata** → **Show metadata** → **Attachments**).

The citation for each dataset is available in the **Metadata** → **Show citation** menu.

The bibliographic citation for FishStatJ is as following:

*FAO Fisheries Division, Statistics and Information Branch. FishStatJ: Universal software for fishery statistical time series. Copyright 2020.*

## 12.3. Data versioning and Data revisions

Where necessary, the data published in the previous releases of the dataset(s) of fishery and aquaculture statistics are revised.

Where figures in this release differ from those previously published, the amended data represent the most recent version. Some statistics provided to FAO by national offices, in particular those for most recent year, are provisional and may be amended in future editions.<sup>4</sup>

An example of the version of FishStatJ is "2020.1.0"

Major version: is the year when the data was released (2017)

Minor version: is the release (1) and revision number (0)

Occasionally, we find errors, or we receive data from member countries after the release of the FishStatJ workspace. In these rare cases, we release a new revision of the data by increasing the revision number. This way, the new version is automatically visible in the **Workspaces Manager** as a new download. In this case, we would also include an explanation in the dataset notes. Refer to section 9.2 how to view dataset notes.

## 12.4. FishStatJ workspace folder

FishStatJ stores imported workspaces (and application files) in the user home directory:

- For Windows, use the **Windows + R** shortcut to open the Run command, enter **%USERPROFILE%\fishstatj\_workspace** and click **OK**
- For macOS Finder enter **~/fishstatj\_workspace** in **Go** → **Go to Folder** menu

The information inside workspace folder is described in detail below.

Refer to section 11.5 how to remove (un-install) FishStatJ.

### 12.4.1. FishStatJ workspaces

Workspaces are stored in the FishStatJ workspace folder. They contain the time-series data, including the reference data (dimensions), and attachments (maps, dataset notes). There is one folder for each workspace installed.

Workspaces can be deleted permanently from disk, by opening the **Manage workspaces** menu and by using the **Delete** button.

### 12.4.2. Workspace metadata folder

The FishStatJ application's log and preferences are stored in the workspace folder, in a sub-folder called ".metadata".

The FishStatJ application log is called ".log".

FishStatJ application preferences are saved in this location:  
.`metadata/plugins/org.eclipse.core.runtime/.settings`

**Note:** on macOS files and folders starting with a dot are invisible. To open the folder enter `~/fishstatj_workspace/.metadata` in **Go** → **Go to Folder** menu. To show files and folders starting with a dot, press the "Command" + "Shift" + "." (period) keys at the same time.

### 12.4.3. Workspace manual folder

The FishStatJ manual is downloaded and opened from the manual folder inside the `fishstat_workspace`. Refer to section 9.2 for more details on the manual.

## 12.5.Un-installing FishStatJ

FishStatJ can be un-installed by deleting the FishStatJ application folder (macOS: the application icon). The Windows application is usually located at: C:\FishStatJ.

FishStatJ stores imported workspaces (data) in the user home directory; these can be deleted as well:

- For Windows enter **%USERPROFILE%\fishstatj\_workspace** in the Run menu
- For macOS Finder enter **~/fishstatj\_workspace** in **Go → Go to Folder** menu

FishStatJ is a cross-platform application and therefore does not use the Windows-registry, it stores all data and settings in the application and user home directory, as described above.

## 12.6.FishStatJ update notification


Starting with version 3.01 FishStatJ has automatic update capability built in. At program launch a very small XML file (~1KB) is downloaded from the FAO web-site. If the download of this file fails, FishStatJ will show a warning message (refer to section 10.6– No internet connection) and will continue to work with the data downloaded locally.

The URL download location of the XML file is shown in preferences, refer to section 4.4.6 - Internet Access.

The XML file enables the following 3 functions in FishStatJ, which are described below.


### 12.6.1.Automatic update notification

When we release a new version of FishStatJ, Windows users will see the following message at program startup; macOS users receive the program update notification shown in 11.6.2:




Clicking the **Start update** button will start the download of the auto-extract file:





Once the download is complete, FishStatJ quits, and the extraction dialog appears:




Clicking the **Yes** button will expand the software, and launch the new version of FishStatJ.

If no internet connection is available at start-up, a message appears (section 10.6– No internet connection).

### 12.6.2. update notification

When we release a new version of FishStatJ, you will see the following message at program startup:



Clicking the **Yes** button will open the FAO FishStatJ web-page in a web browser. On this page, you find the latest FishStatJ application for download.

**Note:** The user has to perform the download of the application program, and install it on the PC. There is no auto-download or auto-update of the application.

If no internet connection is available at start-up, a message appears (section 10.6– No internet connection).

### **12.6.3.Workspace download**

FishStatJ will show new or updated workspaces in the **Manage workspaces** dialog. Using this dialog, the user can choose which workspace to download and install on the PC.

For a description of the workspace management; please refer to section 3.1-Manage workspaces.

Refer to section 12.3 for an explanation of workspace/data versioning.

Available workspaces, their version and download location are contained in the XML file; if no internet connection is available then only workspaces downloaded and installed previously are shown.

### **12.6.4.FishStatJ manual download**

The first time the user manual is opened, or when a new version is available, the PDF manual is downloaded. The version of the manual and download location of the manual is contained in the XML file.

Refer to section 10.2 (**User Manual**) for how to open the FishStatJ manual.

The FishStatJ manuals are downloaded to the workspace folder. Refer to section 12.4.3 (FishStatJ manual folder).

When running offline, the manual can only be opened if it was previously downloaded.

## 12.7. Assistance and Contact

On the FishStatJ web-page ([fao.org/fishery/statistics/software/fishstatj/en](http://fao.org/fishery/statistics/software/fishstatj/en)) you can find

- New program versions for download
- A list of workspaces and their versions available for download using FishStatJ
- A quick-start guide for installing the program
- The download link to this manual
- The e-mail contact for support ([fish-statistics-inquiries@fao.org](mailto:fish-statistics-inquiries@fao.org))